DERWENT-ACC-NO: 2002-251211

DERWENT-WEEK: 200230

COPYRIGHT 1999 DERWENT INFORMATION LTD

Semiconductor package including double underfill

area

INVENTOR: CHUN, J H; NOH, Y H; YOON, H G

PATENT-ASSIGNEE: SAMSUNG ELECTRONICS CO LTD[SMSU]

PRIORITY-DATA: 1999KR-0055694 (December 8, 1999)

PATENT-FAMILY:

LANGUAGE PUB-NO PUB-DATE

PAGES MAIN-IPC

N/A July 2, 2001 KR 2001054743

001 H01L 021/60

Α

APPLICATION-DATA:

APPL-DESCRIPTOR APPL-NO PUB-NO

APPL-DATE

KR2001054743A74 1999KR-0055694 N/A

December 8, 1999

INT-CL (IPC): H01L021/60

ABSTRACTED-PUB-NO: KR2001054743A

BASIC-ABSTRACT: NOVELTY - A semiconductor package including

double underfill

area is provided to prevent a fillet part of underfill area from cracking.

DETAILED DESCRIPTION - A bonding pad (112) is formed on a

semiconductor

chip(110). The bonding pad(112) is connected with the semiconductor chip(110)

through a bump(120). The semiconductor chip(110) is composed of a

substrate(130), an external connection terminal(140) such

as solder balls, and

a double underfill area(150). The double underfill

area(150) consists of the

first underfill area(154) and the second underfill

area(156). The first underfill area(154) locates between the semiconductor chip(110) and the substrate(130), and is filled with liquid type of a sort of epoxy material.

The second underfill area(156) positions around the semiconductor chips(110), and it is reclaimed with a sort of silicon material.

CHOSEN-DRAWING: Dwg.1/10

TITLE-TERMS:

SEMICONDUCTOR PACKAGE DOUBLE AREA

DERWENT-CLASS: U11

EPI-CODES: U11-D01C9;

06/20/2002, EAST Version: 1.03.0002

